

Standard



BNQ 3680-905/2008
(R 2013)

Prefabricated Septic Tanks for Residential Use –
Dimensional and Physical Characteristics



This page has intentionally been left empty.

BNQ 3680-905/2008
(R 2013)

Prefabricated Septic Tanks for Residential Use –
Dimensional and Physical Characteristics

*Fosses septiques préfabriquées pour usage résidentiel –
Caractéristiques dimensionnelles et physiques*

ICS: 13.060.30; 23.020.10

REQUEST FOR INFORMATION AND PURCHASE

Any request for information or purchase of this document may be sent to the Bureau de normalisation du Québec (BNQ) at 333, rue Franquet, Québec, Québec G1P 4C7
[telephone: 418-652-2238, ext. 2437 or 1-800-386-5114; fax: 418-652-2292;
E-mail: bnqinfo@bnq.qc.ca; Web Site: www.bnq.qc.ca].

REVISION OF BNQ DOCUMENTS

Collaboration from BNQ document users is essential in keeping our documents up to date. Therefore, any suggestion aimed at improving their contents will be appreciated. We ask you to send us your suggestions or comments on the form at the end of this document.

SECOND EDITION — 2013-10-02

This is a reaffirmation (reapproval) of the edition dated October 8, 2008.

This document is published in both French and English. In case of incompatibility, the French version prevails.

The systematic review of this document to determine if it has to be modified, revised, reaffirmed or withdrawn will take place no later than at the end of the ninth year following this edition.

The electronic or printed version of this document is for personal use only. Distribution to third parties, partners or clients, as well as saving, distribution or use on a computer network is forbidden without written agreement from the BNQ.

Only purchasers duly registered with BNQ Customer Service will receive document updates. Notifications and the catalogue may be consulted at all times on the BNQ Web site [www.bnq.qc.ca] to verify if a more recent version of a document exists or if amendments or errata have been published.

If a registered purchaser wishes to continue to receive updates, the purchaser must inform BNQ Customer Service of any change of address as soon as possible.

© BNQ, 2013

All rights reserved. Unless otherwise specified, no part of this document may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilming, without written permission from the BNQ.

ISBN 978-2-551-25423-1 (printed version)
ISBN 978-2-551-25424-8 (PDF)

Legal deposit — Bibliothèque et Archives
nationales du Québec, 2013

NOTICE

UNDERSTANDING OF THE NOTION OF EDITION

It is important to note that this edition implicitly includes all the amendments and errata that might eventually be developed, and published separately. It is the responsibility of the users of this document to verify if any amendments or errata exist.

INTERPRETATION

The verb **shall** is used to express a requirement that is mandatory in order to comply with this document.

The verb **should**, or the equivalent expressions **it is recommended that** and **ought to**, are used to indicate a useful, but not mandatory, suggestion, or to provide the most appropriate means of complying with this document.

Except for the notes presented as **normative notes** that contain mandatory requirements and are stated only in the lower part of figures and tables, all other **notes** are **informative** (non-mandatory) and provide useful information pertaining to the understanding or intent of a requirement, or to add some clarification or precision.

Normative annexes provide additional requirements that are mandatory in order to comply with this document.

Informative annexes provide additional information (non-mandatory) intended to assist in the understanding or use of elements of this document or to clarify its implementation, but they contain no requirements that are mandatory in order to comply with this document.

In English-language documents, a period is often used instead of a comma as a decimal marker. Nevertheless, the BNQ has decided to use the comma as the decimal marker in all of the documents published by the BNQ, as is the case with all ISO documents.

DISCLAIMER OF RESPONSIBILITY

This document was developed as a reference document for voluntary use. It is the responsibility of the users to verify if laws or regulations make the application of this document mandatory, or if trade regulations or market conditions stipulate its use, for example, in technical regulations, inspection plans originating from regulatory authorities, and certification programs. It is also the responsibility of the users to consider limitations and restrictions specified in the Purpose and Scope and to judge suitability of this document for their purpose.

REQUIREMENTS FOR MARKING AND LABELLING

It is possible that this document contains requirements for marking and/or labelling. In this event, in addition to meeting these requirements, it is also the responsibility of the suppliers of products to comply with the applicable national, provincial or territorial laws and regulations of the jurisdictions where the products are distributed.

This page has intentionally been left empty.

FOREWORD

The reaffirmation (reapproval) of this document was approved by a Standards Development Committee, whose members were:

BEAULIEU, Yves	Association des ingénieurs municipaux du Québec (AIMQ)
BÉLANGER, Marie-Christine	Premier Tech Environnement
BERGERON, Marie-Claude	Ministère du Développement durable, de l'Environnement, de la Faune et des Parcs (MDDEFP)
BOYER, Normand	Les Blocs Normand inc.
CIMON, Daniel	Corporation des officiers municipaux en bâtiment
GAGNÉ, Jacques	Jacques Gagné experts-conseils inc.
GÉLINAS, Daniel	Xactics (2001) International inc.
GILLES, Claude	Réseau Environnement
LAPOINTE, Hélène	Ordre des ingénieurs du Québec
OTIS, Marc	Béton provincial ltée
ROY, David	Société d'habitation du Québec (SHQ)
ST-PIERRE, Daniel	Matériaux économiques inc.
VÉZINA, Christian	Roy, Vézina et associés
ALLARD, Sylvain (standards developer)	Bureau de normalisation du Québec (BNQ)

The 2008 edition was revised and approved by a Standards Development Committee, whose members were:

BEAULIEU, Yves	Association des ingénieurs municipaux du Québec (AIMQ)
BÉRUBÉ, Yves	Premier Tech Environnement
BOYER, Normand	Les Blocs Normand inc.
CIMON, Daniel	Corporation des officiers municipaux en bâtiment
DUMOULIN, Pierre-Paul	Ordre des ingénieurs du Québec
GAGNÉ, Jacques	Jacques Gagné experts-conseils inc.
GILLES, Claude	Réseau Environnement
LALÉ, Érol	Xactics (2001) International inc.
MORISSETTE, Michel	Ministère du Développement durable, de l'Environnement et des Parcs (MDDEP)
OTIS, Marc	Béton provincial ltée
ROY, David	Société d'habitation du Québec (SHQ)
ST-PIERRE, Daniel	Matériaux économiques inc.
VÉZINA, Christian	Roy, Vézina et associés
GAGNÉ, Nicole (standards developer)	Bureau de normalisation du Québec (BNQ)

The collaboration of Mr. Richard Marois of the Conseil régional de l'environnement de la Montérégie is also worthy of mention.

CONTENTS

	Page	
1	PURPOSE	1
2	SCOPE	1
3	NORMATIVE REFERENCES	1
4	DEFINITIONS	3
5	GENERAL REQUIREMENTS	4
5.1	DESIGN	4
5.1.1	Design Criteria of a Septic Tank	4
5.1.2	Manufacturing Materials	4
5.1.3	Access Openings	4
5.2	SHOP DRAWING	4
6	SPECIFIC REQUIREMENTS	5
6.1	REQUIREMENTS APPLYING TO CONCRETE SEPTIC TANKS	5
6.1.1	Construction of a Concrete Septic Tank	5
6.1.2	Concrete Components	5
6.1.3	Concrete Strength	6
6.1.4	Concrete Mixture Characteristics	6
6.1.5	Concrete Curing	6
6.1.6	Reinforcement	6
6.1.7	Synthetic Macro-Fibres	7
6.1.8	Storage of Materials	7
6.1.9	Joint Between the Reservoir and Cover of the Concrete Septic Tank	7

6.2	REQUIREMENTS APPLYING TO REINFORCED POLYESTER SEPTIC TANKS	8
6.2.1	Reinforced Polyester	8
6.2.2	Additive	8
6.2.3	Gel Coat	8
6.2.4	Reinforcing Material	8
6.2.5	Laminate Layer Quality	8
6.2.6	Interior Layer	9
6.2.7	Structural Layer	9
6.2.8	Exterior Layer	9
6.2.9	Construction and Assembly of Sections	9
6.2.10	Surface Hardness	9
6.2.11	Laminate Joint Construction	9
6.2.12	Edge Treatment	10
6.3	REQUIREMENTS APPLYING TO POLYETHYLENE SEPTIC TANKS	10
6.3.1	Polyethylene Designation Code	10
6.3.2	Use of Polyethylene Residue	10
6.3.3	Quality of the Walls and Components	10
7	DIMENSIONAL AND PHYSICAL CHARACTERISTICS	10
7.1	DIMENSIONAL AND GEOMETRICAL CHARACTERISTICS	10
7.1.1	Dimensions	11
7.1.2	Average Liquid Height (H)	11
7.1.3	Average Inside Width (ℓ)	11
7.1.4	Average Inside Length (L)	11
7.1.5	Determination of the Capacity of a Septic Tank	11
7.1.6	Air Volume	11
7.1.7	Air Space Height (h)	12
7.1.8	Openings for Inlet and Outlet Pipes	12
7.1.9	Inlet and Outlet Devices	12
7.1.10	Chamber Divider	14
7.1.11	Access Openings	15
7.1.12	Wall Thickness	15
7.2	PHYSICAL CHARACTERISTICS	15
7.2.1	Top-Loading Resistance (Static Load)	15
7.2.2	Watertightness	15
8	TEST METHODS	16
8.1	TEST SEQUENCE	16

8.2	CONDITIONING OF A SAMPLE SEPTIC TANK	16
8.3	INSTALLATION METHODS APPLYING TO THE SEPTIC TANK USED AS A SAMPLE	16
8.4	WALL THICKNESS MEASUREMENT	16
8.5	TEST TO MEASURE MINIMUM TOTAL CAPACITY AND MINIMUM EFFECTIVE LIQUID CAPACITY OF A SEPTIC TANK	17
8.5.1	Principle	17
8.5.2	Procedure	17
8.6	TOP LOADING RESISTANCE (STATIC LOAD) TEST APPLYING TO ALL MATERIALS	17
8.6.1	Principle	18
8.6.2	Test Benches	18
8.6.3	Procedure for a Concrete Septic Tank	19
8.6.4	Procedure for a Reinforced Polyester Septic Tank	19
8.6.5	Procedure for a Polyethylene Septic Tank	19
8.6.6	Results	20
8.7	WATERTIGHTNESS TEST	20
8.7.1	Principle	20
8.7.2	Concrete Septic Tank	21
8.7.3	Reinforced Polyester or Polyethylene Septic Tank	21
8.8	RESISTANCE (STATIC LOAD) TEST OF THE PRE-FILTER ATTACHMENT SYSTEM	21
9	MARKING AND HANDLING	22
9.1	MARKING	22
9.2	HANDLING	22
9.3	MAINTENANCE OF THE PRE-FILTER	22
FIGURE 1 —	EFFECTIVE LIQUID CAPACITY OF A SEPTIC TANK	23
FIGURE 2 —	TYPICAL DIMENSIONAL RATIOS OF A CONCRETE SEPTIC TANK	24
FIGURE 3 —	TYPICAL DIMENSIONAL RATIOS OF A CIRCULAR REINFORCED POLYESTER SEPTIC TANK	25
FIGURE 4 —	TYPICAL DIMENSIONAL RATIOS OF A RECTANGULAR POLYETHYLENE SEPTIC TANK WITH ROUNDED ENDS	26

FIGURE 5 —	CONNECTION OF INLET PIPE TO A SEPTIC TANK USING A WATERTIGHT FLEXIBLE SEAL	27
FIGURE 5 —	CONNECTION OF INLET PIPE TO A SEPTIC TANK USING A WATERTIGHT FLEXIBLE SEAL	28
FIGURE 6 —	DETAILS OF THE CONNECTION OF INLET AND OUTLET PIPES TO A CONCRETE SEPTIC TANK USING A WATERTIGHT FLEXIBLE SEAL AND INSTALLATION OF THE CONCRETE DEFLECTOR	29
FIGURE 7 —	DETAILS OF THE CONNECTION OF INLET AND OUTLET PIPES TO A CONCRETE SEPTIC TANK USING A WATERTIGHT FLEXIBLE SEAL WITH THE INSTALLATION OF A PLASTIC BAFFLE	30
FIGURE 8 —	OPEN-TOPPED T FITTING CONNECTED TO THE INLET PIPE	31
FIGURE 9 —	EXAMPLE OF A PRE-FILTER CONNECTED TO AN OUTLET PIPE	32
FIGURE 10 —	CLEARANCE BETWEEN THE CHAMBER DIVIDER, ABOVE DEVICES (INLET AND OUTLET) AND THE CEILING (TOP) OF THE CONCRETE SEPTIC TANK	33
FIGURE 11 —	CHAMBER DIVIDER WITH OPENINGS IN A RECTANGULAR CONCRETE SEPTIC TANK	34
FIGURE 12 —	EXAMPLES OF A TEST BENCH WITH SAND BEDDING EQUIVALENT TO TOP LOADING (STATIC LOAD) RESISTANCE APPLIED TO A CONCRETE SEPTIC TANK	35
FIGURE 13 —	EXAMPLE OF A TEST BENCH EQUIVALENT TO TOP LOADING (STATIC LOAD) RESISTANCE APPLIED TO A POLYETHYLENE SEPTIC TANK	36
FIGURE 14 —	EXAMPLE OF A TEST BENCH EQUIVALENT TO TOP LOADING (STATIC LOAD) RESISTANCE APPLIED TO A POLYETHYLENE SEPTIC TANK	37
FIGURE 15 —	EXAMPLE OF A TEST BENCH EQUIVALENT TO TOP LOADING (STATIC LOAD) RESISTANCE APPLIED TO A REINFORCED POLYESTER SEPTIC TANK	38

FIGURE 16 —	EXAMPLE OF A TEST BENCH SIMULATING A LOAD GENERATED BY A PNEUMATIC MEMBRANE EQUIVALENT TO TOP LOADING (STATIC LOAD) RESISTANCE APPLIED TO A REINFORCED POLYESTER OR POLYETHYLENE SEPTIC TANK	39
ANNEX A —	PHYSICAL PROPERTY OF LAMINATE	40
TABLE A.1 —	MINIMUM VALUES	40
ANNEX B —	JOINT LAP WIDTH BASED ON LAMINATE THICKNESS	41
TABLE B.1 —	DIMENSIONS	41
ANNEX C —	RUBBER SEALANT BEAD	42
TABLE C.1 —	PHYSICAL CHARACTERISTICS	42
ANNEX D —	METHOD TO CALCULATE AVERAGE INSIDE LENGTH (L), AVERAGE INSIDE WIDTH (ℓ) AND AVERAGE LIQUID HEIGHT (H) OF A SEPTIC TANK	43
FIGURE D.1 —	SEPTIC TANK — DETERMINATION OF DIMENSIONS	44
ANNEX E —	INSTALLATION OF A RISER	46
FIGURE E.1 —	EXAMPLE 1	46
FIGURE E.2 —	EXAMPLE 2	46
ANNEX F —	POINTS TO BE CONSIDERED FOR STRUCTURAL ANALYSIS OF DESIGN AND CONSTRUCTION OF A SEPTIC TANK	47
ANNEX G —	INFORMATIVE REFERENCE	48

This page has intentionally been left empty.

PREFABRICATED SEPTIC TANKS FOR RESIDENTIAL USE — DIMENSIONAL AND PHYSICAL CHARACTERISTICS

1 PURPOSE

This standard specifies the dimensional and physical characteristics of prefabricated septic tanks for residential use made of concrete, glass fibre-reinforced polyester or polyethylene.

2 SCOPE

This standard applies to prefabricated septic tanks intended for underground installation to receive wastewater, including household wastewater, before its evacuation towards a purification device, drainfield or wastewater treatment system.

NOTE — The *Regulation respecting waste water disposal systems for isolated dwellings* [as amended] (see Annex G) provides directives concerning the installation of prefabricated septic tanks.

This document was developed to serve as a reference document for conformity evaluation activities of specific products.

NOTE — Conformity evaluation is defined as the systematic examination of the extent to which a product fulfils specified requirements.

3 NORMATIVE REFERENCES

For the purpose of this document, the following reference documents contain necessary requirements and are referred to in appropriate places in the text:

BNQ (Bureau de normalisation du Québec) [www.bnq.qc.ca]

NQ 2560-114-IV/2002

*Travaux de génie civil — Granulats — Partie IV :
Béton de masse volumique normale.*

NQ 2621-900/2002

*Bétons de masse volumique normale et
constituants.*